

Technical Specifications (continued)

Construction

Lens:

Prismatic Acrylic Lens

Mounting:

Surface mount. Can be mounted with v-hooks (ordered separately).

Finish:

Formulated for high durability and long-lasting color

Green Technology:

Mercury and UV free. RoHS-compliant components.

Other

5 Yr Limited Warranty:

The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.


Equivalency:

Equivalent to (4) F32T8

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions



Features

Affordable, easy to use LED wrap fixture

0-10V dimming standard

50,000-Hour LED lifespan

Ordering Matrix

| Family | Length | Wattage | Color Temp | Finish | Voltage | Control Options | Options | |
|--------|----------------------|----------------------------------|---|-----------|-----------------------------|---|---|--|
| GUSJR | 4 | - | 40 | - | 840 | W | U | |
| | 2 = 2 ft 4 = 4 ft | 20 = 20W 27 = 27W 40 = 40W | 850 = 5000K (Cool) 840 = 4000K (Neutral) 835 = 3500K (Warm Neutral) | W = White | U = 120-277V, 0-10V Dimming | Blank = No Option /LC = Lightcloud® Controller | Blank = No Option /E2 = 120-277V Battery Backup* /TW = Through Wire | |

* Only available in 4FT (27W or 40W)